

Axpert MAX Off-Grid Inverter



- Customizable status LED bar with RGB lights
- Built-in wifi for mobile monitoring (Android/iOS Apps are available)
- Supports USB On-the-Go function
- Reserved communication port for BMS (RS485, CAN-BUS or RS232)
- Replaceable fan design for ease of maintenance
- Battery independent design
- Configurable AC/PV output usage timer and prioritization
- Selectable high power charging current
- Selectable input voltage range for home appliances and personal computers
- Compatible to Utility Mains or generator input
- Built-in anti-dust kit
- Optional DC output for DC fan, LED bulb, router and so on
- Parallel operation up to 6 units only available for 7.2kVA




RGB light:
Different color to present output source from PV, Grid or battery and battery charge/discharge status



Communication for Remote panel



Parallel connectors:
Maximum 6 units in parallel (only for MAX-7200)



Diverse communications:
USB On-the-Go function, Dry contact and BMS communication



Anti-dust filter:
Increase product reliability in harsh environment



DC output connectors:
Connect to DC fan, LED bulb or router



Axpert MAX Off-Grid Inverter Selection Guide

MODEL	Axpert MAX 3600-24-230	Axpert MAX 3600-24-120	Axpert MAX 7200-48-230	Axpert MAX 7200-48-120
Rated Power	3600VA/3600W		7200VA/7200W*	
PARALLEL CAPABILITY	NO		Yes, up to 6 units	
INPUT				
Voltage	230 VAC	120 VAC	230 VAC	120 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)	90-140 VAC (For Personal Computers) 80-140 VAC (For Home Appliances)	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)	90-140 VAC (For Personal Computers) 80-140 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)			
OUTPUT				
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%	120VAC ± 5%	230VAC ± 5%	120VAC ± 5%
Surge Power	7500VA	7500VA	15000VA	15000VA
Efficiency (Peak)	90% ~ 93%			
Transfer Time	15 ms (For Personal Computers) ; 20 ms (For Home Appliances)			
Waveform	Pure sine wave			
No Load Power Consumption	< 45W		< 70W	
BATTERY				
Battery Voltage	24 VDC		48 VDC	
Floating Charge Voltage	27 VDC		54 VDC	
Overcharge Protection	33 VDC		66 VDC	
SOLAR CHARGER & AC CHARGER				
Solar Charger Type	MPPT			
Maximum PV Array Power	4000 W		8000W (4000W x 2)	
MPPT Range @ Operating Voltage	120 ~ 450 VDC	90 ~ 230 VDC	90 ~ 450 VDC	90 ~ 230 VDC
Maximum PV Array Open Circuit Voltage	500 VDC	250 VDC	500 VDC	250 VDC
Maximum Solar Charge Current	80 A			
Maximum AC Charge Current	80 A			
Maximum Charge Current	80 A			
PHYSICAL				
Dimension, D x W x H (mm)	147.4 x 432.5 x 553.6			
Net Weight (kgs)	14.1		18.4	
Communication Interface	USB/RS232/RS485/Wifi/Dry-contact			
OPERATING ENVIRONMENT				
Humidity	5% to 95% Relative Humidity(Non-condensing)			
Operating Temperature	-10°C to 50°C			
Storage Temperature	-15°C to 60°C			
STANDARD				
Compliance Safety	CE	UL	CE	UL

* 120 VAC model rated as 5000VA when unit operated under invert mode
Product specifications are subject to change without further notice.